CLAIMS

What I claim is:

5

10

15

1. A tool for use in removing door hinge pins, said tool comprising:

an elongate barrel having a first end and a second end, said barrel defining a slot originating at said first end and longitudinally extending toward said second end;

a sturdy base fixed to said barrel second end;

a push rod having a first end connected to said base and projecting axially within said barrel;

whereby a door hinge pin may be removed by slidably positioning the tool on a door hinge such that said push rod is axially aligned with the hinge pin and striking said base with a blunt object thereby causing said push rod to at least partially eject the pin from the door hinge.

2. A tool according to claim 1, wherein said barrel further defines a window for allowing a user to view alignment of said push rod with the pin of a door hinge.

3. A tool according to claim 1, wherein said slotted aperture is tapered proximate said barrel first end.

20

5

10

15

20

- 4. A tool according to claim 1, wherein said base defines a notch for use in removing caps from hinge pins.
 - 5. A tool for use in removing door hinge pins, said tool comprising:

an elongate barrel having a first end and a second end, said barrel defining a slot originating at said first end and longitudinally extending toward said second end, said barrel further defining a window;

a sturdy base fixed to said barrel second end;

a push rod having a first end connected to said base, a mid portion projecting axially within said barrel, said push rod terminating at a second end;

said window longitudinally aligned with said push rod second end;

whereby a door hinge pin may be removed by slidably positioning the tool on a door hinge such that said push rod is axially aligned with the hinge pin and striking said base with a blunt object thereby causing said push rod to at least partially eject the pin from the door hinge.

- 6. A tool according to claim 5, wherein said base defines a notch for use in removing caps from hinge pins.
- 7. A tool according to claim 5, wherein said barrel first end defines a tapered portion forming the mouth of said notch.